



Options, Configurations and Pricing

Evo Basic Time Clock



Information
next.timetac.com



TimeTac Evo Basic Time Clock

Upgrade your time tracking system with our modern employee time clocks. Record arrivals, departures, and breaks effortlessly with fingerprint or RFID/NFC technology. Conveniently placed by doors or in receptions, our time clocks offer a sleek solution for attendance tracking. Unified data storage allows seamless tracking from multiple devices and easy access to reports on the go or at the office. Ideal for environments where computers or smartphones are not practical, such as factories and hospitals. Make time tracking hassle-free with our reliable hardware solution.

- ① 200×109×85mm casing
- ② Colour-LCD 800×480px display with touch screen
- ③ Customisable display options for optimal usage
- ④ RFID or RFID + optional fingerprint reader
- ✓ Easy to wall mount
- ✓ LAN or optional WLAN connectivity
- ✓ IP54 Protection

Configurations and Pricing

The Evo Basic Time Clock offers you different configurations to choose from. All of these time clocks include a TCP/IP LAN network card, wall mounting fixtures and a power cable. When ordering time clocks, please consider that configurations must be conducted by our hardware supplier and cannot be performed on-site.

Terminal Evo Basic with RFID/NFC-Reader**



from £ 25.90 monthly*

Further Configurations and Additions

Time Clock Configurations

- Fingerprint Reader** £ 9.90*
- POE (Power over Ethernet) Adapter*** £ 2.50*
- WLAN Module - 802.11bg and 802.11n £ 6.90*

Additions

- RFID/NFC Key Ring (one time, net price per piece) £ 2.90

* Monthly rental fee, with a yearly plan. All stated prices are net.

** 13.56 MHz RFID/NFC Reader (ISO 14443: Mifare-Classic, MifareDesfire, -Plus, Ultralight). Readers for other RFID standards available if required.

*** Supported: IEEE 802.3af und IEEE 802.3at

Technical Details

Casing	Structure	Plastic casing ABS HB
	Dimensions (height x width x depth)	200 × 109 × 85 m
	Weight (w/o power supply)	Base unit 0.35kg plus wall mount plate of 0.125kg
Display	LCD	TFT 3.5" [8.9 cm] 800 × 480 pixels incl. proximity sensor for automatic activation in sleep mode
Power Supply	Power	12 V DC
Environment values	Ambient temperature	-20°C to + 60°C
	Protection	IP54 front
Data transmission	TCP / IP (optional)	TCP / IP operating with integrated TCP / IP stack, 10/100 Mbit
	WLAN (optional)	Integrated wireless LAN module, WIFI 802.11 bg and 802.11n (Only 2.4 GHz)
	USB	Micro-USB for setup of data transmission
	Details	<ul style="list-style-type: none">• via HTTPS, DHCP as per default• DNS per default 8.8.8.8, individual settings possible• The ports 443 und 8000 have to be released. Port 443 for data transmission to gt.timetac.com and port 8000 for maintenance connection on dfa.timetac.com
Additional Options	Fingerprint (optional)	Fingerprint module; sensor in lower right of housing
	Transponder reader	125KHz - Unique, titanium, Hitag. 13,56 MHz - Legic, Mifare, ISO14443, ISO15693, SimonsVoss, iButton, Nedap

next.timetac.com

info@timetac.com

A large graphic featuring the text "because time matters" in a bold, black, sans-serif font. The text is enclosed within a thick black rectangular frame that has a notch at the top-left and bottom-left corners. Behind the text, there are two large, overlapping circular shapes: a large orange one at the top and a smaller blue one at the bottom.

DE/AT: 0800 - 240 40 50

Int. +43 (0)316 587142

ES: +34 900 751400