



KIN S - SM - B01



BATTERY OPERATED, SURFACE MOUNTED STRIKE WITH INTEGRATED KINDOO ACCESS CONTROL

Compatible with 1/2" throw latchbolt. No power supply required.

The KIN S - SM - B01 is battery operated, surface mounted electric strike with an integrated KINDOO access control system. Simply fix the strike to the surface of the frame and connect it to the provided activation pad and battery pack.

No Cutting Required. No Internet Connection Required. No External Wiring Required.

Batteries Last up to 100,000 Openings. 7 Years Battery Lifetime Based on 30 Daily Openings.

Strike Features

- Non Handed
- Stainless Steel 304
- Static strength 1,500 lbs
- Dynamic strength 70 ft-lbs
- Endurance 250,000 cycles
- Wood and Metal Frames
- No Cutting Required
- Up to 1/2" latch
- 32°F to 120°F (0°C to 49°C)
- Dimensions: 8 7/8" x 1 3/4" x 5/8"

Access Control Features

- Up to 30 ft range (without obstacles)
- Industry leading 256 bit encryption
- Bluetooth® low energy - 2.4 GHz frequency
- KINDOO app available for iOS® and Android™
- All functions controlled from the KINDOO smartphone app
- Add/delete users and control access rights
- Manage access schedules
- Review audit trail logs
- Grant access remotely
- Turn ON/OFF access events notifications
- Customize transaction messages
- Changes you make are effective immediately

Battery Holder Features

- 4 x CR123 Batteries (not included)
- Wall Mounted
- VHB Double Sided Tape
- Stainless Steel 304
- 50°F to 120°F (10°C to 49°C)
- 1 5/8" x 3 7/8" x 1"

Activation Pad Features

- Wall Mounted
- HB Double Sided Tape
- Stainless Steel 304
- IP 65 rated
- 0°F to 120°F (-20°C to 50°C)
- 1 1/8" diameter

US Patents: US11861960B1, US10325430B2, US12196005

© 2024 KINDOO LLP. All Rights Reserved.