



CARE . TRUST . RESPONSIBILITY

# RECEIPT PRINTER RP-330

FAST AND QUIET PRINTING



The printer RP-330 is a thermal receipt printer solution for retail and hospitality environments that require fast and quiet printing. Furthermore it supports a full range of fonts for different countries.

The compact size and integrated wall mounting make the reliable model ideal for many applications. A wide range of interfaces and port options allow easy installation and simple integration to either POS environments or POS solutions.

Equipped with a signal tone the PR-330 can be remotely controlled and making it ideal for kitchen uses.

## SPECIAL FEATURES

- 8MB Flash Logo RAM
- 80mm paper width
- 200mm/sec high speed printing
- Support full & partial cut
- Wall mounting

## OPTIONAL

- Paper near end sensor

RP-330

**RP-330**

MODELL	RP-330		
Printing Method	Direct thermal		
Printing Speed	200mm/sec. text printing 200mm/sec. graphic printing		
Dot Density	180dpi		
Dot Pitch	0.141mm		
Paper	Type: thermal paper, black mark Width: 58~82.5mm Print width: 72mm max. Roll ø: 80mm Roll core inner ø: 12mm ± 0.5mm		
Sensor	Paper end, cover open, paper near end Optional: black mark sensor		
I/O Interface	Standard: USB (B type), cash drawer Optional Interfaces: Serial, Parallel, Ethernet		
Memory	RAM: 8MB Flash: 2MB		
Auto Cutter Type	Guillotine (full cut, partial cut, tear-off)		
Reliability	Print head: 160km Cutter: 1.500.000 cuts MCBF: 60.000.000 lines MTBF: 360.000 hours		
Power Supply	100~240V / AC 50/60Hz / DC24V ± 10%, 1.75A		
Environment	Temperature: Humidity:	Operating: 5°C ~ +40°C 10% ~ 90%	Storage: -20°C ~ +60°C 10% ~ 90%
Driver	Windows (XP, 7, 8.1, 10) Linux OPOS (Windows 32/64bit)		
Dimensions	152mm (W) x 198mm (D) x 151mm (H)		
Weight	1.7kg		
Options	Optional interfaces: serial, parallel, ethernet black mark sensor		
Color	black or white		

\*Specification is subject of change without prior notice. May19

