

SP-635

SP-635-E**Economical and Efficient POS Terminal****FEATURES**

- Powerful Intel® Celeron™ J6412 Elkhart Lake processor
- Supports up to 32GB RAM
- Flexible modular design and dual display support
- Spill and dust resistant front panel, IP65
- Convenient VESA / wall mount and wide tilt angle monitor
- Green low power consumption

SP-635

PARTNER

Specifications



Item	SP-635-E
Size	15"
Aspect Ratio	4:3
Resolution	1024 x 768
Brightness	350 nits
Touch	PCAP Touch
CPU	Intel® Celeron® J6412 (Elkhart Lake)
Memory	DDR4 4GB, 8GB, 16GB, 32GB
Storage	2.5" SATA SSD: 128G / 256G / 512G
I/O Interface	4 x serial ports, RS232 (DB9), 0V/5V/12V selected in BIOS (COM1, COM2, COM3, COM4) 1 x LAN (IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC +12V out 4 x USB 3.2 1 x DC +12V input 1 x audio (1 x line-out) + mic in 1 x VGA
Speaker	1 x speaker (3W)
Peripheral Options	MSR, IC Card reader, fingerprint reader, RFID/ NFC, i-Button, VFD, USB 2nd display, VGA/HDMI 2nd display
Wireless Option	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.2
Display Support	2 independent displays (Main Display + VGA)
Spill & Dust Resistant	IP54 Certified
Operating System	1. Windows 11 IoT Enterprise GAC (64bit) ready 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04
TPM	S/W TPM 2.0 (BIOS)
Power Adaptor	AC-In 100~240V / DC-Out 12V, 65W / 90W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F
Dimensions (Wx Hx D)	360 x 365 x 240 mm / 14.17 x 14.37 x 9.45 in
Weight	5,24 kg

*Specification is subject to change without prior notice

Contact Now

Germany +49 40 450 635-0
United Kingdom +44 1928 579 707
Spain +34 913 120632
Sloga +386 1 566 25 20
Polen +48 22 115 93 82

info@partner-tech.eu
sales-uk@partner-tech.eu
comercial@partner-tech.eu
prodaja@partner-tech.eu
officepoland@partner-tech.eu