

Audrey

A7 Series**Touch POS Terminal****FEATURES**

- Sleek and modern design
- All in one POS with PCAP 21.5" screen
- Latest high-performance Intel CPU with fanless design
- Front panel IP65, whole device IP54 certified
- High speed M.2 SSD
- Supports Win IoT Enterprise and Linux

Audrey

Specifications



	A7-1-AL	A7-1-E
Size	21.5"	
Aspect Ratio	16:9	
Resolution	1920 x 1080	
Brightness	300 nits	
Touch	PCAP Touch	
CPU	Alder Lake-P Intel® Core™ i3-1215U Intel® Core™ i5-1245U, vPro Intel® Core™ i7-1265U, vPro	Elkhart Lake Intel® Celeron® J6412
Memory	DDR4 4GB, 8GB, 16GB, 32GB	
Storage	M.2 PCIe SSD: 128G / 256G / 512G	
I/O Interface	3 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3) 1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC +12V out 4 x USB 3.2 + 2 x USB 2.0 1 x DC +12V input 1 x audio (1 x line-out) 1 x HDMI 1 x Type-C (data transfer + display)	
Speaker	1 x speaker (3W)	
Peripheral Options	MSR, fingerprint reader, RFID/NFC, i-Button, VFD, USB 2nd display, HDMI 2nd display, 2D bar code scanner, camera, IO extension box (EX-100, EX-101, EX-300), cash drawer, PS-103 Cosmo printer stand (space-saving stand, compatible with RP-700 or Epson TM-T70 II)	
Wireless Option	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.2	
Display Support	3 independent displays (Main Display + HDMI + Type-C)	
Spill & Dust Resistant	Front panel IP65, whole unit IP54 certified	
Operating System	1. Windows 11 IoT Enterprise GAC (64bit) ready 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04	
TPM & vPro	1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS)	S/W TPM 2.0 (BIOS)
Power Adaptor	AC-In 100~240V / DC-Out 12V, 120W	AC-In 100~240V / DC-Out 12V, 90W / 120W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F	
Dimensions (Wx Hx D)	522 (W) x 376 (H) x 201 (D) mm / 20.55 x 14.8 x 7.91 in	
Weight	10 kg / 22.04 lb	

*Specification is subject to change without prior notice

Contact Now

Germany +49 40 450 635-0
 United Kingdom +44 1928 579 707
 Spain +34 913 120632
 Sloga +386 1 566 25 20
 Polen +48 22 115 93 82

info@partner-tech.eu
sales-uk@partner-tech.eu
comercial@partner-tech.eu
prodaja@partner-tech.eu
officepoland@partner-tech.eu