

RP-710

RP-710**Printer**

FEATURES

- Cubic type housing 125*131.5*125mm(W*D*H) ideal for front or top exit paper out applications
- e.g. Kiosk, SCO, under desk etc.
- supports IAP online upgrade, voice Broadcast, replaying, queuing function
- Optional: Bluetooth Smart Ready (Bluetooth5.0+BLE) or WiFi(802.11 a/b/g/n) B/T, WF combo

RP-710



Specifications

	RP-710
Color housing	Black/(White project based)
Print speed	Up to 250mm/s (9.8 ips)
Paper type	Thermal receipt paper/black mark supported
Paper roll	58mm, 80mm, 82.5mm max. outer diameter Φ 83mm (3.2")
Paper thickness	0.05-0.08mm
Print width	80mm (640 dots/line)
Dot Pitch/ Resolution	0.125x 0.125mm, 203 dpi
Characters per line (CPL)	Font A (12x24) – 53/48/35 columns, Font B (9x17) – 71/64 /46 columns
Line space	3.75mm (adjustable by command)
Print command	Compatible with ESC/POS commands
Interface type	Standard: USB(B type)+Serial(RS- 232C_9pin)+Ethernet Built-in Option (project based): Bluetooth Smart Ready(Bluetooth5.0+BLE)and/or WiFi(802.11 a/b/g/n)
Character size	ANK character, Font A: 1.5mm~3.0mm (12~24 points)Font B: 1.1mm~2.1mm (9~17 points)
Figure	Monochrome BMP and other image files can be downloaded to FLASH
Bar-code type	1D: EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar, QR Code, PDF41
Emulation/Driver	ESC/POS , Windows Driver(XP ~, Server2003 ~),Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, Android SDK, iOS SDK, Windows SDK
Extended character list	PC437(Std.Europe), (Katakana), PC850(Multilingual), PC860(Portugal), PC863(Canadian),PC865(Nordic), (West Europe), (Greek), (Hebrew), (East Europe), (Iran), (WPC1252), PC866(Cyrillic#2), PC852(Latin2), (PC858), (IranII), (Latvian), (Arabic), (PT1511251)
Reliability	MCBF 80 million lines/ TPH Life 150 km
Sensor	Paper end, Cover open/black mark
Cutter Type/ Method/Life	Guillotine/partial_full cut/2.000.000 cuts
Input buffer/NV Flash	128Kbytes/256Kbytes

RP-710

Specifications

	RP-710
Power adapter voltage input/output	AC 100-240V/50~60Hz/ DC 24V/2.5A
Cashdrawer control	2 circuits, DC 24V/1A(max)
Environment	Work T: 0°C ~45°C; H: 10%~80%/Storage T: -10~60°C; H: 10~90% (non-condensate)
Physical: Size/Net weight	125*131.5*125mm(W*D*H)/0.90kg (TBD)

Contact Now

Germany	+49 40 450 635-0	info@partner-tech.eu
United Kingdom	+44 1928 579 707	sales-uk@partner-tech.eu
Spain	+34 913 120632	comercial@partner-tech.eu
Slovenia	+386 1 566 25 20	prodaja@partner-tech.eu
Poland	+48 22 115 93 82	officepoland@partner-tech.eu