



CARE . TRUST . RESPONSIBILITY

DP-101A

THE MULTIFUNCTIONAL DISPLAY



The 10.1" DP-101A is a compact, stylish and modern POS monitor. Its light weight and aluminum alloy housing is ideal for a variety of installation environments. It fits perfectly in many business areas such as retail, hospitality and many more. The monitor can be used as a customer display, with or without touch, as operator display as well as for digital signage purposes. Customer information or advertising become a more and more increasing demand in many business cases. The DP-101A can be attached as a 2nd monitor on many of our POS terminals or as a stand-alone version through the optional stand or long pole options. Here the monitor is adjustable in height and can be fixed easily in required position by the individual operator. With the VESA mounting compatibility the installation options of the DP-101A are endless.

SPECIAL FEATURES

- 10.1 inches LCD with LED backlight
- 1280 x 800 WXGA resolution
- Elegant design with aluminum alloy housing
- USB or VGA interfaces
- Supports VESA mounting

OPTIONAL

- USB or VGA interface
- 10-point PCAP Touch
- Aluminum Zig Zag stand
- Long Pole Stand

DP-101A

MODELL		DP-101A
Monitor	Max. Resolution	1280 x 800
	Size	10.1"
	Brightness	280 nits
	Contrast	500:1
	Display Colors	16.7M
	Response Time	20 ms
	LED Backlight Life	20.000 hours
	Viewing Angle	Right 75° Left 75° / Upper 75° Lower 75°
	Technology	LCD with LED backlight
	Touch (optional)	10-point PCAP Touch (USB touch)
Interfaces	USB version	1 x USB dual input (for power, video and touch) 3 Buttons (Up & Down for brightness, Power Button)
	3 Buttons (Up & Down for brightness, Power Button)	1 x RJ11 (for touch) 1 x VGA 1 x Power Jack 5 Buttons (Exit, Up, Down, OSD Menu, Power Button)
Dimensions	without stand	253.9 mm (W) x 179.0 mm (H) x 38.3 mm (D)
Weight	without stand	1.02 kg
Environment	Operating Temperature	0°C ~ 40°C
	Storage Temperature	-20°C ~ 55°C
	Operating Humidity	10% ~ 80%
	Storage Humidity	10% ~ 80%
Others	Colors	black; silver
	VESA Mounting	75 x 75
	Material	Aluminum Alloy housing
	Certifications	CE, FCC
	Power Adapter	External power adapter 12V 2A DC (Only for VGA version)
	Cable	USB version: 1 x 2-in-1 USB
Optionen	Stands	Long Pole Stand; Aluminum Zig Zag stand
	Touch	10-point PCAP touch (USB touch)
	LED Backlight Life	50.000 hours

*Specification is subject of change without prior notice. Jan 19