



# PINK NEXT GEN™ FIBERGLAS® INSULATION

Owens Corning® PINK NEXT GEN™ FIBERGLAS® Insulation is a preformed, unfaced, and flexible blanket insulation designed for friction-fit installation in wood or steel frame cavities. It is produced in RSI (R-values) from 2.1 (R-12) to 9.5 (R-54), with thicknesses ranging from 89 mm (3-1/2 inches) to 406 mm (16 inches).

## Basic Uses/Related Uses

- Wood-framed wall, floor, and roof/ceiling cavity wall applications
- Metal-framed wall and floor cavity wall applications
- Interior surfaces of basement and unvented crawl space foundation walls

## Selection Criteria

- Excellent thermal control
- Effective acoustical control
- Long-term performance and will not settle or slump within wall cavities
- With less dust than other fiberglass products, PINK NEXT GEN™ FIBERGLAS® insulation has excellent stiffness and recovery characteristics
- Compression packaging from Owens Corning speeds job site handling and installation

## Performance Criteria

<b>COMPLIANCE:</b>	Evaluation Report No. 05650-L Type 1 Type 1	CCMC CAN/ULC-S702 ASTM C665
<b>THERMAL:</b>	See Sizes and R-values	CAN/ULC-S702
<b>FIRE:</b>	Non-Combustible Smoulder Resistance Average Mass Loss ≤ 2%, Individual Mass Loss ≤ 3% Flame Spread 0; Smoke Developed 0 Flame Spread 0; Smoke Developed 0	CAN/ULC-S114 CAN/ULC-S129  CAN/ULC-S102 CAN/ULC-S102.2
<b>MOISTURE:</b>	Fungi Resistance (pass)	ASTM C1338
<b>CORROSION:</b>	Steel, Aluminum, Copper (non-corrosive)	ASTM C665

## Technical Information

- For optimum insulation performance, the building thermal barrier (insulation) should be in continual alignment with the building air barrier. In framed cavities, the product thickness should match the depth of the framing members.
- Follow the local, applicable building code(s) to determine the need for and placement of a vapour retarder.
- Building, electrical, fire and other applicable codes shall be complied with. All heat emitting devices, such as fuel burning appliances, chimneys, pipes, ducts and vents to these appliances shall maintain a minimum clearance of 50 mm (2 in.) between these devices and the insulation. Recessed light fixtures, unless designed for the purpose, shall not be installed in insulated ceilings.
- Deliver products in their original packages, and store in enclosed shelter.
- Packaging is not UV resistant. Shelter-unused packages from the elements.
- Ensure applicator's personnel wear protective equipment such as breathing mask (dust-proof type mask), eye protection (safety goggles or eye glasses), and skin protection (gloves, long-sleeved shirts, and pants) when handling and applying materials. Wash with soap and warm water after handling. Wash work clothes separately and wipe out washer. For additional information refer to Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>.

## Sizes

THERMAL RESISTANCE		APPLICATION	THICKNESS	WIDTH	LENGTH	COVERAGE/BAG			
RSI	R					SQ. M.	SQ. FT.		
2.1	12 <sup>2</sup>	Wood Frame	89 mm (3.5")	279 mm (11")	1219 mm (48")	13.65	146.7		
						381 mm (15")	1194 mm (47")	9.10	97.9
							1219 mm (48")	9.29	100.0
							1346 mm (53")	10.25	110.4
							1194 mm (47")	11.53	124.0
						584 mm (23")	1194 mm (47")	13.95	150.1
1219 mm (48")	14.24	153.3							
Steel Frame	92 mm (3.625")	406 mm (16")	1219 mm (48")	9.91	106.7				
				610 mm (24")	14.86	160.0			
2.4	14	Wood Frame	89 mm (3.5")	381 mm (15")	1194 mm (47")	7.28	78.3		
		Steel Frame	92 mm (3.625")	584 mm (23")	413 mm (16.25")	1219 mm (48")	11.16	120.1	
3.5/3.3	20/19 <sup>2</sup>	Wood Frame	152/140 mm (6"/5.5")	279 mm (11")	1219 mm (48")	10.91	117.3		
						381 mm (15")	1194 mm (47")	7.28	78.3
							1219 mm (48")	7.43	80.0
							1346 mm (53")	8.21	88.4
							1194 mm (47")	9.22	99.2
						584 mm (23")	1194 mm (47")	11.16	120.1
1219 mm (48")	11.40	122.7							
3.5	20	Steel Frame	152 mm (6")	406 mm (16")	1219 mm (48")	7.93	85.3		
						610 mm (24")	11.89	128.0	
3.9	22	Wood Frame	140 mm (5.5")	381 mm (15")	1194 mm (47")	4.55	49.0		
						483 mm (19")	1346 mm (53")	5.13	55.2
							1194 mm (47")	5.77	62.0
							584 mm (23")	6.97	75.1
4.0	22.5	Steel Frame	152 mm (6")	413 mm (16.25")	1219 mm (48")	5.03	54.2		
						3.13	33.7		
4.2	24	Wood Frame	140 mm (5.5")	375 mm (14.75")	1194 mm (47")	4.83	52.0		
		Steel Frame	152 mm (6")	578 mm (22.75")	413 mm (16.25")	1219 mm (48")	3.52	37.9	
4.9	28	Unrestricted Cavity <sup>5</sup>	216 mm (8.5")	381 mm (15")	1219 mm (48")	4.64	50.0		
						406 mm (16")	4.95	53.3	
						483 mm (19")	5.89	63.4	
						610 mm (24")	7.43	80.0	
		Cavity Restricted <sup>6</sup>	178 mm (7")	381 mm (15")	1219 mm (48")	2.79	30.0		
						584 mm (23")	4.27	46.0	
5.4	31	Unrestricted Cavity <sup>5</sup>	235 mm (9.25")	406 mm (16")	1219 mm (48")	3.96	42.7		
						610 mm (24")	5.95	64.0	
6.1	35	Unrestricted Cavity <sup>5</sup>	267 mm (10.5")	406 mm (16")	1219 mm (48")	3.47	37.3		
						610 mm (24")	5.20	56.0	
7.0	40 <sup>3</sup>	Unrestricted Cavity <sup>5</sup>	279 mm (11")	406 mm (16")	1219 mm (48")	2.97	32.0		
						279 mm (11")	610 mm (24")	4.46	48.0
	40 <sup>4</sup>	Unrestricted Cavity <sup>5</sup>	300 mm (11.8")	406 mm (16")	1219 mm (48")	2.97	32.0		
						300 mm (11.8")	610 mm (24")	4.46	48.0
9.5	54	Unrestricted Cavity <sup>5</sup>	406 mm (16")	610 mm (24")	1219 mm (48")	3.72	40.0		

<sup>2</sup>R-12 and R-20 48" long batts for wood frame construction are available in Quebec only. Contact your Area Sales Manager for additional sizes and regional availability. <sup>3</sup>Available in Western Canada. <sup>4</sup>Available in Eastern Canada. <sup>5</sup>Unrestricted Cavity: Available depth of cavity can be greater than insulation thickness. <sup>6</sup>Cavity Restricted: Available depth of cavity is same as insulation thickness.

## Certifications and Sustainable Features

- Certified by SCS Global services to contain an average 73% recycled content with minimum 61% post-consumer and balance 12% pre-consumer
- GREENGUARD Gold Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg)
- UL Environment validated Formaldehyde-Free
- Product specific Type 3 UL Environmental Product Declaration (EPD) has been certified by UL Environment
- Participating in Declare- Living Building Challenge Compliant
- Contributes to credits in green building programs such as LEED® and Green Globes. For further information see documents: LEED® v4 for Building Design and Construction and Owens Corning Impact Study - Leadership in Energy and Environmental Design (LEED® v4).



## Environmental and Sustainability

Owens Corning is a worldwide leader in building material systems, insulation, and composite solutions, delivering a broad range of high-quality products and services. Owens Corning is committed to driving sustainability by delivering solutions, transforming markets, and enhancing lives. More information can be found at [www.owenscorning.ca](http://www.owenscorning.ca) or [www.owenscorninglibrary.ca](http://www.owenscorninglibrary.ca).

### Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with particular uses of any product described herein.

SCS Global Services provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit [www.SCSglobal.com](http://www.SCSglobal.com).

LEED® is a registered trademark of the U.S. Green Building Council.

### Notes

Fibreglass products may cause temporary skin and mucous membrane itching due to the mechanical abrasion effects of fibres, a condition which is completely reversible. Owens Corning does not recommend the use of unfaced PINK NEXT GEN™ FIBERGLAS® insulation in exposed applications where it will be subject to routine human contact due to this potential temporary irritation.

For additional information, refer to the Safe Use Instruction Sheet (SUIS) found in the SDS Database via <http://sds.owenscorning.com>

## Technical Services Available

For Canadian Technical inquiries please contact local representative. See Technical territory map via [www.specowenscorning.ca/contacttech](http://www.specowenscorning.ca/contacttech).



Current Ed: 2021-06-01  
Previous Ed: 2021-06-01

**OWENS CORNING CANADA LP**  
3450 MCNICOLL AVENUE  
SCARBOROUGH, ONTARIO M1V 1Z5

**1-800-GET-PINK®**  
[www.owenscorning.ca](http://www.owenscorning.ca)

Pub. No. 501224. Printed in Canada. June 2021.  
THE PINK PANTHER™ & © 1964–2021 Metro-Goldwyn-Mayer Studios Inc.  
All Rights Reserved. The colour PINK is a registered trademark of Owens Corning.  
© 2021 Owens Corning. All Rights Reserved.