SIEMENS

Data sheet 6GT2821-6AC32

product type designation



RF260R reader IO-Link

SIMATIC RF200 reader RF260R IO-Link; IO-Link interface; IP67, -25 to +70 °C; 75x 75x 40 mm; with integrated antenna 8 byte IO; 38.4 Kbit/s.

suitability for operation	ISO 15693 transponder (MDS Dxxx), for connecting to IO-Link Master V1.0	
adio frequencies		
operating frequency / rated value	13.56 MHz	
range / maximum	135 mm; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964	
protocol / with radio transmission	ISO 15693, ISO 18000-3	
transfer rate / with radio transmission / maximum	26.5 kbit/s	
product feature / multitag-capable	No	
lectrical data		
transfer rate / at the point-to-point connection / serial / maximum	38.4 kbit/s	
transmission time / for user data		
 for write access / per byte / typical 	40 ms	
• for read access / per byte / typical	40 ms	
data volume / of the address range of the inputs / total	8 byte	
data volume / of the address range of the outputs / total	8 byte	
nterfaces		
standard for interfaces / for communication	IO-Link V1.0	
type of electrical connection	M12, 4-pin	
nechanical data		
material	PA6.6	
color	anthracite	
tightening torque / of the screw for securing the equipment / maximum	1.5 N·m	
mounting distance / relating to metal surfaces / recommended / minimum	0 mm	
upply voltage, current consumption, power loss		
supply voltage / at DC		
rated value	24 V	
•	20.4 28.8 V	
consumed current / at DC		
• at 24 V / typical	0.05 A	
mbient conditions		
ambient temperature		
during operation	-20 +70 °C	
during storage	-25 +80 °C	
during transport	-25 +80 °C	
protection class IP	IP67	
shock resistance	EN 60721-3-7 Class 7 M2	
shock acceleration	500 m/s²	
vibrational acceleration	200 m/s ²	

design, dimensions and weights	
width	75 mm
height	41 mm
depth	75 mm
net weight	0.2 kg
fastening method	2 x M5 screws
wire length	
 between master and IO-Link device / maximum 	20 m
product features, product functions, product components / gene	eral
display version	3-color LED
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
certificate of suitability	
• IECEx	No
MTBF	480 a
standards, specifications, approvals / Environmental Product De	eclaration
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	43.51 kg
during manufacturing	10.7 kg
during operation	32.51 kg
after end of life	0.3 kg
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
to web page: RFID country approval	https://www.siemens.com/rfid-approvals
 to web page: identification and localization systems 	https://www.siemens.com/ident
to web page: SiePortal	https://sieportal.siemens.com/
to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAx-Download-Manager	https://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval







Declaration of Conformity



China RoHS

General Product Approval	MV	Radio Equipment Type Approval Certificate	Environment	
--------------------------	----	---	-------------	--

Manufacturer Declara-
tionKCMiscellaneous
ECMiscellaneous

EPD

last modified: 3/25/2025 🖸